




SPRING BUMPER



KICKPLATE



DOUBLE DUTCH

- 1 - TOP HINGE ASSEMBLY
- 2 - BOTTOM HINGE ASSEMBLY
- 3 - ANODIZED ALUMINUM FRAME PROFILE
- 4 - 9" WIDE x 14" HIGH CLEAR SAFETY ACRYLIC WINDOW
- 5 - 1/4" THICK ABS DOOR BODY

*** RECOMMENDED FRAMING REQUIREMENTS:
 1/8" THICK x 4" WIDE FACE STEEL FRAME MOUNTED
 TO A SOLID FOUNDATION.

DOOR OPENING:
 _____ W x _____ H

DOUBLE SINGLE

QUANTITY: _____

COLOR: _____

OPTIONS

(CHECK BOX IF APPLICABLE)

- 5/16" THICK HDP SPRING BUMPERS
 (UP TO 42" HIGH)

- CUSTOM WINDOW DESIGN

RECTANGULAR _____ W x _____ H

ROUND - DIAMETER: _____

- 9 1/4" JAMB GUARDS

- KICKPLATES: (UP TO 48" HIGH)

1/4" ABS

- CART GUARD

ABS

- DOUBLE DUTCH

S. S. QUOTE REF. # _____

CUSTOMER _____

APPROVED BY: _____

P/O No.: _____

DATE: _____



SERIES 1500 - MODEL 1504
 ABS IMPACT DOOR

DATE: NOV-23-04 SCALE: 1:24

DRAWN: OC DWG NO: L1504